

PATENT APPLICATION

POOL TABLE SLATE LIFTER

5

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of the filing of U.S. Provisional Patent Application Serial No. 60/240,261, entitled POOL TABLE SLATE LIFTER, filed on October 12, 2000, and the specification thereof is incorporated herein by reference.

10

BACKGROUND OF THE INVENTION

Field of the Invention (Technical Field):

The present invention relates to pool table or billiard table slate lifters and to the methods of using such lifters.

15

Background Art:

20

Pool and billiard tables are comprised of two main components: a cabinet housing and a slate which forms the actual playing surface. A slate is a unitary, typically rectangular, planar material that is usually composed of a very dense, heavy material. The weight of the slate often causes a structural creep with in the cabinet (sag). Additionally, general use of the table results in wear of a fabric covering the slate. As a result repairs are periodically needed to the table to place shim materials on the various slate supports to accommodate for the sag. Removal of the fabric covering for replacement is also periodically required. These periodic repairs are very difficult to accomplish given the weight and unwieldiness of the slate. In the past, removal of a slate could only be accomplished with the combined manpower of two or more people. The present invention can be used by a single person and does not

25 require the user to exert a great deal of physical force in its operation.

Other than the unwieldy nature of the slate, the slate's configuration and composition presented additional concerns for its manipulation. If any structural deficiencies are present in the slate, the

pressures applied by lifting the slate at one point, especially on an angle and on only one side, can result in the cracking or breaking of the slate. Prior art slate lifters such as the device disclosed in U.S. Patent No. 5,340,083 to Suhy et al., utilize a jack type apparatus that is inserted at one point under the slate and is used to lift the slate from one side. Therefore, the slate is lifted on an angle with the non-lifted side
5 bracing against the cabinet. This type of device is not best suited for lifting a large, heavy planar material such as a slate since the forces exerted at the single lift point could stress the slate resulting in cracking or breaking. The present invention utilizes multiple lift points on opposing sides of the slate thereby minimizing stress to the slate.

10 The '083 patent device, while accomplishing lift, is unsuitable to allow a single user to lift a slate entirely. The device utilizes only one lift point, requiring the user to operate the device on one side of the table at a time. The slate is lifted and whatever repairs are possible are performed on the lifted side. The slate is then lowered, and the device is disengaged. The device is then moved to the opposite side of the table, and the process begins again. This is a time consuming inconvenience that is avoided by
15 the present invention.

Further, the '083 device, which braces one edge of the slate against the table while lifting the opposing side, may shift at its brace points, requiring the user to hold the slate at all times to prevent slipping. The present invention provides a mechanism that does not require the user to hold the slate in
20 place to prevent possible "slips" that could harm the slate, the table, or the user.

Lifting devices for slabs that are not specifically designed for pool table slates are known in the art. U.S. Patent No. 4,962,913 to Stewart discloses a device for lifting sidewalk slabs for repair. The device comprises a rigid longitudinal span supported over the sidewalk with cross members. Winches
25 are employed on the cross members to raise hooks disposed on cables. The '913 patent discloses separate winches for each cross member without interrelation other than potentially utilizing adjacent switch operation of each winch or providing a master control switch. Such adjacent switches or even a master switch cannot ensure synchronous, concurrent operation of the winches. As a result, the slab will

not be maintained in a horizontal position throughout the lifting process. This destabilizes the load, introducing the potential for loss of the load during the lifting process. The lifting mechanism of the present invention overcomes this problem.

5 SUMMARY OF THE INVENTION (DISCLOSURE OF THE INVENTION)

The present invention is a lifter that may be used in combination with a pool or billiard table (hereinafter referred to as "pool table" or "table") to easily and safely lift and lower a pool table slate into position on the cabinet frame slate supports. The apparatus utilizes a frame comprising at least four side support brackets which each having an upper end and a lower end and at least two cross support beams which have opposing ends. The cross support beams are connected to the side support brackets near or at the upper ends of the brackets and near or at the opposing ends of the cross support beams. This places the beams and brackets in a perpendicular position relative to one another.

The present invention has support brackets with an upper assembly on their upper ends, including a support frame opening provided for inserting the cross beams therethrough.

The lifter may additionally include upper and lower crossbeam guides adjacent to the opening. A support bracket brace with a side support frame hole for receipt of a crossbeam table width adjustment pin may also be provided. The cross support beams may comprise a plurality of adjustment holes disposed near each of the opposing ends of the beam for receipt of the crossbeam table width adjustment pin.

The lifter also has raising and lowering mechanism comprising winches, a power transmission shaft, drop pulleys, cables, and slate clamps. Alternate mechanisms for lifting such as hydraulic systems may be utilized. A winch is provided at an approximate midpoint of each cross support beam. The winch utilized is preferably a drum winch. The winch nearest the power source comprises a master winch; the other winches are slave winches. A non-circular transmission shaft is disposed through each winch and torque applied to the shaft is transferred to the winch. The winches have at least one cable,

which has opposite ends, disposed through each winch. The cable is also threaded through at least one pulley. These drop pulleys are disposed at points on the cross support beams which are interposed between a midpoint of the cross support beams and a point of intersection of the beams and the support brackets. At least two drop pulleys are disposed on each cross support beam. At least one spring loaded hook is attached to each protruding end of the cable. The hooks are engaged with the slate, preferably at points correlating to the positioning of pockets within the frame of the table. A power source is connected to a near end of the transmission shaft and is capable of applying torque to the shaft which is then transferred to the winches for raising and lowering the slate. The power source is preferably a motor, however other sources capable of torquing a shaft, including a manually generated force, may be utilized.

In a case where a manually generated force is utilized as the power source, the lifter preferably further includes a worm gear disposed at a near end of the power transmission shaft. The gear has a noncircular bore which is attachable to the transmission shaft in a manner sufficient to provide a transfer of the torque to the shaft. The torque is provided by operation of a crank handle having a crank end and a connection end. The handle is connected to a worm at the connection end, and the worm is positioned in relationship to the worm gear to transfer torque from the crank handle to the worm gear and finally to the transmission shaft.

The present invention adjusts to multiple table sizes, where the height of the support brackets, the length of the transmission shaft, and the length of the cross support beams are adjustable. The lifter preferably comprises six brackets and three beams. However, other configurations having at least four brackets and two beams are also within the scope of the present invention.

Stabilizing devices may be utilized, including a clamp on the support bracket for attachment to a table. A leg extension may extend below the upper surface of the cabinet frame of a pool table. A support foot may be attached to and adjacent the lower end of the support bracket. Side support beams

may be attached in a perpendicular planar configuration with the brackets which may be adjustably connected to the brackets so that the overall length of the apparatus is adjustable.

The slate lifter is preferably used in combination with a pool table. The slate lifter comprises side support brackets having a lower end which has a bottom surface that rests on an upper edge of the cabinet frame of the pool table.

The present invention further comprises a method of operating a slate lifter by placing a bottom surface of the side support brackets on an upper edge of a pool table cabinet. The height of the side support brackets is adjusted, as is the length of the power transmission shaft and cross support beams. These positions are then fixed into place, and slate hooks are attached under a bottom surface edge of the table in relationship with the pockets. A torque force is applied to the transmission shaft and is contemporaneously transferred from the shaft to a master winch and at least one slave winch to provide synchronous movement. Finally, a cable attached to the slate hooks and threaded through the winch and pulleys is winched to either raise or lower the slate.

A primary object of the present invention is to provide a slate lifter that lifts a pool table slate.

Another object of the present invention is to provide a stable slate lifter that can be attached to a pool table.

A further object of the present invention is to provide a slate lifter that is easily operated either manually or through power devices.

Another object of the present invention is to provide a slate lifter that does not require great physical strength in the user.

A further object of the present invention is to provide a slate lifter that does not place undue stress on the slate or to the pool table cabinet.

Yet another object of the present invention is to provide a slate lifter that is easily storable.

5

Another object of the present invention is to provide a slate lifter that is adjustable to different sizes of tables and slates.

A primary advantage of the present invention is the ability to lift a slate and keep it horizontal, thereby reducing stress on the slate and allowing a user to repair either the slate covering or table on opposing sides of the table without additional operations.

Another advantage of the present invention is the easy assembly, storage, and use of the invention.

Yet another advantage of the invention is the adjustability of the invention to the length and width parameters of tables of differing size.

Other objects, advantages and novel features, and further scope of applicability of the present invention will be set forth in part in the detailed description to follow, taken in conjunction with the accompanying drawings, and in part will become apparent to those skilled in the art upon examination of the following, or may be learned by practice of the invention. The objects and advantages of the invention may be realized and attained by means of the instrumentalities and combinations particularly pointed out in the appended claims.

25

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated into and form a part of the specification, illustrate one or more embodiments of the present invention and, together with the description, serve to

explain the principles of the invention. The drawings are only for the purpose of illustrating one or more preferred embodiments of the invention and are not to be construed as limiting the invention. In the drawings:

5 Fig. 1 is perspective view depicting the slate lifter of the present invention used with a standard pool table;

 Fig. 2 is a side view of an upper assembly of the side support brackets for connection with the cross support beams;

 Fig. 3 is a end view of the slate lifter illustrating the support assembly and lifting mechanism;

 Fig. 4 is a side view of the side support brackets illustrating the upper assembly and a lower assembly for supporting and stabilizing the apparatus;

 Fig. 5 is a perspective view of the intersection of the cross beams and support brackets, additionally depicting a pulley on the cross beam; and

 Fig. 6 is a perspective view of the lifter folded for storage.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

(BEST MODES FOR CARRYING OUT THE INVENTION)

The present invention is a lifter and method for its use. It is particularly useful for lifting slates from pool tables. It comprises a support assembly for stabilizing a lifting mechanism over a slate. The support assembly, typically comprising side support brackets and cross support beams, is preferably adjustably connected to accommodate various sizes of tables. Additional side support beams and stabilization members, including bracket feet, leg extensions, or clamps, may be utilized to hold the apparatus solidly on the table cabinet frame. The lifting mechanism preferably includes a non-circular

transmission shaft connecting a series of winches disposed on cross beams. The winches are threaded with cables attached to clamps which hold the slate and winch the cables to raise or lower the slate. The invention may also utilize other lifting mechanisms such as a hydraulic system.

5 Reference is now made to the drawings which illustrate embodiments of the present invention.

Fig. 1 is a perspective view depicting pool table slate lifter **10** that is preferably used in combination with pool table **12** preferably having generally rectangular cabinet frame **14** with four corners **16**, having corner pocket **18** disposed at each corner, and four side walls **20** comprising two longer side walls **22**, having at least one side pocket **24** disposed approximately at a midpoint on each of longer side walls **22**, and two shorter side walls **26**. The table also has slate **28** comprising playing surface **30**, having upper surface **32**, lower surface **34**, and four edges **36**. The lifter apparatus of the present invention is useful for lifting and lowering slate **28** vertically while keeping it in a relatively horizontal position. Additionally, the apparatus of the present invention does not require tilting the slate to gain access to the underside of the slate or interior **38** of cabinet **14**.

Fig. 1 depicts a preferred embodiment of slate lifter **10** having support assembly **40** and lifting mechanism **42**. Support assembly **40** preferably comprises six upright brackets **44** and three cross beams **46**. Differing numbers of brackets and cross beams are utilized, but it is preferable to use at least four brackets and two cross beams for stability of the apparatus. Both upright brackets **44** and cross beams **46** are detachable from lifter **10** to allow for adjustability of the apparatus. Brackets **44** and beams **46** comprise a suitably rigid material to support the weight of slate **28**. Preferably the material is a metal, and more preferably steel is utilized for its strength and light weight. Lifting mechanism **42** comprises power transmission shaft **48** in perpendicular arrangement with cross beams **46** and disposed through winches **50**. Master winch **52** is preferably disposed nearer power source **54** than slave winches **56**. All winches **50** are disposed approximately at a midpoint of cross beams **46**. Winches **50** are preferably drum winches and operate in a reversible manner. Additionally, it is preferred to have winches which will not release the cable without utilizing a manual release switch, thereby preventing the

slate from falling if the winching action is halted. Winches **50** have at least one cable **58** threaded therethrough. Cable **58** is additionally threaded through at least one pulley **60**. Pulley **60** is preferably a drop pulley. Additionally, each cross beam **46** has at least two pulleys **60**. Each pulley **60** is interposed at a point between the midpoint of cross beam **46** and ends **62** of cross beam **46**. Each cable **58** has a clamp **64** attached to its at least one protruding end **66**. Clamps **64** are preferably spring loaded clamps. Clamps **64** are attached to slate **28**, preferably at points corresponding to pockets **18**, **24**.

Fig. 2 is a side view of brackets **44** which preferably comprise upper assembly **68** for connection with cross beams **46**. Upper assembly **68** comprises support frame opening **70** for inserting cross beams **46** therethrough. Upper assembly **68** additionally comprises upper crossbeam guides **72** and lower crossbeam guides **74** adjacent opening **70**. Further depicted is adjustment hole **76** on side support bracket brace **78** for receipt of pin **80** for connection with crossbeams **46**.

Fig. 3 is an end view illustrating support assembly **40** and lifting mechanism **42**. The invention utilizes crank **82**, having crank end **84** and connection end **86** for effecting manual power source **54**. Connection end **86** is connected to worm **88** which is in relationship with worm gear **90** sufficient to transfer torque from crank **82** to worm gear **90**. Worm gear **90** turns, thereby torquing power transmission shaft **48**. Power transmission shaft **48** is disposed through winches **50**. Fig. 3 depicts drum winch **50** with cable **58** threaded therethrough. Cable **58** is additionally threaded through drop pulley **60** and has spring loaded clamps **64** attached to each end **66**. Fig. 3 further depicts cross beams **46** inserted through opening **70** of bracket **44** and utilizing plurality of adjustment holes **76** with pin **80** for connection. Further depicted is foot **92** on bracket **44** for added stability. Other stability devices may be utilized in further embodiments, including clamps and leg extensions.

Fig. 4 is a side view of brackets **44** depicting upper assembly **68** for connection with cross beams **46** and lower assembly **94** utilizing leg extensions **96**. Upper assembly **68** provides upper guide **72** and lower guide **74** for receipt of cross beam **46**. Lower assembly **94** provides leg extensions **96** for stability. Two extensions **96** are preferably utilized, however, other extension embodiments may be used,

including embodiments having only one extension. The diagram shows two embodiments each utilizing one extension **96** on opposing ends **98** of bracket base **100** and an embodiment utilizing two extensions **96**.

5 Fig. 5 is a perspective view depicting the intersection of the brackets **44** and beams **46** and pulley **60**. Beam **46** is inserted through opening **70** of upper assembly **68** of bracket **44**. Housing **102** of pulley **60** is comprised of at least two side plates **104** having a pulley housing upper crossbeam guide **106**, interposed therebetween. The guide **106** rests on an upper surface **108** of cross beam **46** for disposal along beam **46** at a desired point. Cable **58** is threadedly engage through pulley **60**. One end of the threaded cable **58** is further disposed through winch **50** and the other is engaged by clamp **64**. Preferably, one cable **58** extends between two clamps **64** disposed through two pulleys **60** with engagement in an interposed winch **50** therebetween (See Fig. 1).

10 Fig. 6 is a perspective view support assembly **40** of slate lifter **10** in its storable configuration. Depicted are brackets **44** in an upright position with beams **46** in a horizontal position to brackets **44**. The adjustable connected nature of the apparatus, as depicted here with a pin and hole connection, supports such a configuration.

15 Although the invention has been described in detail with particular reference to these preferred embodiments, other embodiments can achieve the same results. Variations and modifications of the present invention will be obvious to those skilled in the art and it is intended to cover in the appended claims all such modifications and equivalents. The entire disclosures of all references, applications, patents, and publications cited above are hereby incorporated by reference. The invention is not limited to lifting slates from pool tables; it can be used for lifting any applicable surface.